




WE ARE THE AIR WE BREATHE

The UV FAN series is a range of **professional air purifiers** with fans, that guarantees microbial reduction percentage rates, up to 99.99% for each passage of air inside the device, **tested by Independent Laboratories.**


The air can be purified **24 hours per day in presence of people**, thus guaranteeing people's complete protection against airborne pathogens, including bird flu H5N1, SARS, Sars-Cov-2, Herpes, Legionella Pneumophila, TBC, but also Bacteria, Yeasts, Moulds, and Fungi.




Different versions available, for a perfect fit in any room.

KEY PRODUCT FEATURES


- **UV-C germicidal chamber shielded inside** the device, to maximize air treatment and safely use the device in presence of people.
- Silent built-in fan, for use in **all working and educational contexts.**
- **Radio Control** (optional) to turn on/off the device.
- **Inspection porthole** in polycarbonate resistant to UV-C, to safely check the lamps in operation.
- 99,97% reduction of SARS-COV-2, **tested and certified** by Specialized and Independent lab.
- **Increased Disinfection Performance**, with High-Output UV-C lamps (253,7 nm) and internal mirror bright aluminum reflector.
- **“Smart” connectivity** (optional, with smart plug), to integrate the device and control it remotely with any compatible mobile App for smartphone and tablet.
- **Low costs solution** for both energy consumption and maintenance, to be used in combination with natural ventilation




UV-FAN2-95HP



UVFN2-95HP-ST



UV-FAN2-95HP-BD



UVFN2-95HP-ST-BD



HEALTHCARE
PRIVATE - PUBLIC



HVAC - AIR
CONDITIONING SYSTEMS



FOOD AND PHARMACEUTICAL
PRODUCTION INDUSTRY



HOSPITALITY
INDUSTRY



SHARED SPACES
SCHOOLS - OFFICES - SHOPS



LARGE
ENVIRONMENTS



GYMS -
WELLNESS CENTRES



TRANSPORT

TECHNICAL TABLE

FEATURES	AIR PURIFIERS (WALL OR CEILING)				AIR PURIFIERS (WALL OR CEILING) + DIRECT IRRADIATION	
	UV-FAN2-95HP				UV-FAN2-95HP-BD-Rc2	
	UVFN2/95HP	-H	-RC	-HRC	UV-FAN2-95HP-BD-Rc2	-H
Basic	with hour counter	with radio control	with hour counter and radio control	with radio control	with hour counter and radio control	
LAMP LIFE (HOURS)*	≤ 18.000				≤ 18.000	
REPLACEMENT LAMP	2x GHP-95WH				2x GHP-95WH + 1x CHS-90WH (external lamp)	
LAMP POWER (W)	2x 95W				2x 95W + 1x 90W (external lamp)	
DIMENSION	1040 x 320 x 150 mm (41 x 13 x 6 in)				1040 x 397 x 150 mm (41 x 16 x 6 in)	
WEIGHT NOISE	13 Kg (29 Lb) 45 dB				16 Kg (35 Lb) 45 dB	
VOLUME OF AIR TREATED	150 m³/h (88.29 CF/M)				150 m³/h (88.29 CF/M)	
PROTECTION RATING	IP 20				IP 20	
ELECTRICAL CONNECTION	Power supply cable (3x1mm²) length 2m, with IEC socket and SCHUKO plug				Power supply cable (3x1mm²) length 2m, with IEC socket and SCHUKO plug	

FEATURES	MOBILE AIR PURIFIERS ON WHEELS				MOBILE AIR PURIFIERS ON WHEELS + DIRECT IRRADIATION	
	UVFN2-95HP-ST				UV-FAN-M2/95HP-2BD-ST-Rc2	
	UVFN2/95HPST	-H	-RC	-HRC	UVFN2/95HP2BDSTRc2	-H2
Basic	with hour counter	with radio control	with hour counter and radio control	with radio control	with hour counter and radio control	
LAMP LIFE (HOURS)*	≤ 18.000				≤ 18.000	
REPLACEMENT LAMP	2x GHP-95WH				2x GHP-95WH + 2x CHS-90WH (external lamps)	
LAMP POWER (W)	2x 95W				2x 95W + 2x 90W (external lamps)	
DIMENSION	1278 x 397 x 335 mm (50 x 16 x 13 in)				1278 x 470 x 355 mm (50 x 19 x 13 in)	
WEIGHT NOISE	28 Kg (62 Lb) 45 dB				32 Kg (71Lb) 45 dB	
VOLUME OF AIR TREATED	150 m³/h (88.29 CF/M)				150 m³/h (88.29 CF/M)	
PROTECTION RATING	IP 20				IP 20	
ELECTRICAL CONNECTION	Power supply cable (3x1mm²) length 2m, with IEC socket and SCHUKO plug				Power supply cable (3x1mm²) length 2m, with IEC socket and SCHUKO plug	

* continuous operation

TROUBLE-FREE INTEGRATION AND INSTALLATION



- Mounting and powering the device can be done without complex requirements.
- Ongoing maintenance only takes a few minutes to replace lamps when necessary.


TECHNICAL DRAWINGS

Every Light Progress Product is available in detailed DWG and STEP files for your design-in and specification clarity.

VIEW or DOWNLOAD now



MICROBIAL TESTS AND EFFICACY



99,97% reduction of SARS-COV-2 virus, tested and certified by Specialized Labs.

Light Progress customers rely on our extensive history of third party testing and proven efficacy to meet any level of disinfection validated against literally any virus or microorganism.

We understand your need to meet Regulatory Requirements and Industrial Standards as we help you achieve microbial load reduction using our UV systems.

Light Progress Group SRL
Anghiari (AR) ITALIA
P: (+39) 0575 749255
E: info@lightprogress.it
W: www.lightprogress.it

Light Progress GmbH
Aschaffenburg DEUTSCHLAND
P: (+49) 6021-8663700
E: info@lightprogress.it
W: www.lightprogress.de

Light Progress LLC
Austin, TX USA
P: (+1) 833-882-4255
E: americas@lightprogress.it
W: www.lightprogress.us

OFFICIALLY DISTRIBUTED BY:



Component s.r.o.
Bulharská 42, Trnava
IČO: 50 545 361
IC DPH: SK2120375312
Tel. 090 376 33 400
WWW.COMPONENT.SK