


## THE EFFECTIVE, EASY FIT.

Adding a UV device at any stage along AC is always useful, UV STYLO-X is the **simplest and most versatile solution** with its minimal size, easy and flexible installation as one unit or more units combined.


Lamp replacement and **maintenance can be done without dismantling** the system from the duct.

Install as many as you want and create UV section in any AC system.



## KEY PRODUCT FEATURES

- **Ideal for Retrofit**, modules with Flange, easy to install in any ductwork, with many sizes and wattages available.
- **Combine More Devices** and organize them to build your disinfection solution.
- **Increased Disinfection Performance**, with a High-Output UV-C lamp (253,7 nm) enclosed in a Quartz Sleeve, to increase disinfection performances and protect the lamp from temperatures fluctuations.
- **Built to Last, with high-quality Stainless Steel AISI 304**, all material are tested to resist UV.
- **Protected, IP40 Rating**, UVLON™ available to avoid glass falling.
- **Optimized Efficacy with TiOx® filter**, which contributes significantly to the deodorizing action of UV-C. (optional)
- **Choose the Best Power Supply options**, from a simple open frame ballast to a separate control board available for advanced management of multiple lamps.



Healthcare sector  
(hospitals - clinics)



HVAC -  
Air conditioning systems



Food and pharmaceutical  
production industry



Ho.Re.Ca.



Schools -  
Offices - Shops



Large environments



Gyms -  
Wellness centres



Transport

# TECHNICAL TABLE

	UV-STYLO-X						
	UVSTYLOX11	UVSTYLOX16	UVSTYLOX25	UVSTYLOX40 H	UVSTYLOX60 H	UVSTYLOX90 H	UVSTYLOX120H
<b>LAMP LIFE (hours)*</b>	≤ 18.000						
<b>LAMP POWER (W)</b>	11	16	25	40	60	90	120
<b>FLANGE DIMENSION</b>	77x75 L=150mm (3x3 L=6 in)						
<b>HANDLE</b>	D=47 L=100 mm (D=2 L=4 in)						
<b>LAMP SHOULDER</b>	196 mm (8 in)	272 mm (11 in)	500 mm (20 in)	397 mm (16 in)	541 mm (21 in)	851 mm (34 in)	1132 mm (45 in)
<b>WEIGHT</b>	0.20 Kg 0.4 Lb	0.30 Kg 0.7 Lb	0.75 Kg 1.7 Lb	0.70 Kg 1.5 Lb	0.75 Kg 1.7 Lb	0.80 Kg 1.8 Lb	1,00 Kg 2.2 Lb
<b>AIR FLOW IN m³/h WITH SPEED MAX 2.5 m/s</b>	120-320 m³/h (4.238 -11.301 ft³/h)	170-450 m³/h (6.003 -15.892 ft³/h)	250-600 m³/h (8.829 -21.189 ft³/h)	380-1000 m³/h (13.420 -35.315 ft³/h)	650-1700 m³/h (22.955 -60.035 ft³/h)	900-2400 m³/h (31.783 -84.755 ft³/h)	1100-2900 m³/h (38.846 -102.413 ft³/h)
<b>PROTECTION RATING</b>	IP 40						
<b>POWER SUPPLY</b>	4 Options available, including Control Board for the management of multiple lamps, with power supply, access security, hour counter, UV lamp fault control and LED synoptic						
<b>ELECTRICAL CONNECTION</b>	Power supply cable (4x1 mm²), lenght 0,3 m, with quick-fit plug/socket system (3800 series) (IP67). Extension cable can be purchased separately.						

\* continuous operation

## TROUBLE-FREE INTEGRATION AND INSTALLATION



- We provide the optimal point of integration for every product without requiring changes to your system.
- Mounting and powering the device can be done without complex requirements.
- Ongoing maintenance only takes a few minutes to replace lamps when necessary.

## SOFTWARE ENGINEERED DISINFECTION

From our in-depth know-how on the subject and with our proprietary dosage calculation software we can simulate device performance and validate effectiveness in every application.

Calculation Software




## TECHNICAL DRAWINGS

Every Light Progress Product is available in detailed DWG and STEP files for your design-in and specification clarity.

VIEW or DOWNLOAD now



## MICROBIAL TESTS AND EFFICACY



**Up-to log3 microbial reduction on Airflow, Coils and HVAC surfaces, 24 hours a day.**

Light Progress customers rely on our extensive history of third party testing and proven efficacy to meet any level of disinfection validated against literally any virus or microorganism.

We understand your need to meet Regulatory Requirements and Industrial Standards as we help you achieve microbial load reduction using our UV systems.

**Light Progress Group SRL**  
Anghiari (AR) ITALIA  
P: (+39) 0575 749255  
E: info@lightprogress.it  
W: www.lightprogress.it

**Light Progress GmbH**  
Aschaffenburg DEUTSCHLAND  
P: (+49) 6021-8663700  
E: info@lightprogress.it  
W: www.lightprogress.de

**Light Progress LLC**  
Austin, TX USA  
P: (+1) 833-882-4255  
E: americas@lightprogress.it  
W: www.lightprogress.us

**OFFICIALLY DISTRIBUTED BY:**



**Component s.r.o.**  
Bulharská 42, Trnava  
IČO: 50 545 361  
IČ DPH: SK2120375312  
Tel. 09031633 480  
WWW.COMPONENT.SK